

Product: [70065CH](#) 



Life Cycle Status: Discontinued
4 x QUAD SNAKE,26AWG, LSZH-C

Product Description

AUDIO 4 x QUAD SNAKE,26AWG/0.14mm², LSZH-C

Technical Specifications

Product Overview

Suitable Applications:	4 fold star-quad FRNC microphone cable
------------------------	--

Product Life Cycle

Life Cycle:	Discontinued - the product is no longer manufactured
-------------	--

Construction Details

Conductor

Size	Stranding	Material
26	Stranded	BC - Bare Copper

Insulation

Material	Nom. Insulation Diameter	Color Code
PE - Polyethylene	1.15 mm (0.0453 in)	White & Blue & White/Blue & Blue/White
		1, 2, 3, 4

Inner Shield

Shield Type	Material	Coverage
Tape	Bi-Laminate (Alum+Poly)	100%

Inner Shield Table Notes:	Aluminum inside
---------------------------	-----------------

Inner Jacket

Material	Nom. Diameter	Color
LSZH - Low Smoke Zero Halogen (Flame Retardant)	3.70 mm (0.146 in)	Gray (like RAL 7001)

Inner Jacket Table Notes:	Elements are numbered 1-4 for identification
---------------------------	--

Outer Jacket

Material	Nom. Thickness	Nom. Diameter
LSZH - Low Smoke Zero Halogen (Flame Retardant)	1.40 mm (0.0551 in)	11.70 mm (0.4606 in)

Electrical Characteristics

Electricals

Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Shield
110.0 Ohm/km (33.53 Ohm/1000ft)	164 pF/m (50.0 pF/ft)	222 pF/m (67.7 pF/ft)

Mechanical Characteristics

Bend Radius

Installation Min.

117 mm (4.61 in)

Standards and Compliance

Environmental Suitability:	Indoor
Flammability / Reaction to Fire:	IEC 60332-3-24

History

Update and Revision:	Revision Number: 0.259 Revision Date: 03-13-2026
----------------------	--

Part Numbers

Variants

Item #	Color	Putup Type	Length
70065CH.00100	Black	Reel	100 m
70065CH.00500	Black	Reel	500 m
70065CH.001000	Black	Reel	1,000 m

© 2026 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.