



Product: [9451PS4](#) 

Audio Snake Cable, 4 Pair 22 AWG, TC, Indiv. Shielded, CMP

Product Description

Audio Snake Cable, 4 Pair 22 AWG tinned copper pairs, FEP insulation, drain, individually shielded with Beldfoil® bonded to numbered PVC jackets so both strip simultaneously, Plenum Flamarrest® jackets, Banana Peel construction

Technical Specifications

Product Overview

Suitable Applications:	Recording Studio, Radio Broadcast, Sports Stadium, Nurse Call
------------------------	---

Construction Details

Conductor

Size	Stranding	Material	No. of Pairs
22	7x30	TC - Tinned Copper	4

Insulation

Material	Nom. Insulation Diameter	Color Code
FEP - Fluorinated Ethylene Propylene	0.044 in (1.1 mm)	Black & Red

Inner Jacket

Element	Material	Nom. Diameter	Color
Individual	PVC - Polyvinyl Chloride	.127 in (3.23 mm)	Black

Outer Shield

Shield Type	Material	Coverage
Tape	Bi-Laminate (Alum+Poly)	100%

Outer Jacket

Material	Material Trade Name
Banana Peel (No Overall Jacket)	Flamarrest®

Overall Cable Diameter (Nominal):	.306 in (7.77 mm)
-----------------------------------	-------------------

Electrical Characteristics

Delay

Nom. Velocity of Prop.
69%

Voltage

UL Voltage Rating
300 V RMS

Mechanical Characteristics

Temperature

UL Temperature	Operating
60°C	-20°C To +75°C

Max. Pull Tension:	108 lbs (49.0 kg)
Bulk Cable Weight:	68 lbs/1000ft (100 kg/km)

Standards and Compliance

Environmental Suitability:	Indoor - Plenum, Indoor
Flammability / Reaction to Fire:	NFPA 262
NEC / UL Compliance:	CMP
CEC / C(UL) Compliance:	CMP
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

Product Notes

Notes:	The jacket and shield are bonded so both can be removed on automatic stripping equipment. Drain wire is inside foil shield.
--------	---

History

Update and Revision:	Revision Number: 0.517 Revision Date: 09-07-2025
----------------------	--

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC
9451PS4 0101000	Black	Reel	1,000 ft	612825253105

© 2026 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.