

Product: [9498](#) 



Life Cycle Status: Discontinued

Audio, Control and Instrumentation, 3 Conductor 16 AWG, Unjacketed

Product Description

3 Conductor 16 AWG stranded (19x29) tinned copper conductors, conductors cabled, PVC insulation, cabled wire (no jacket).

Technical Specifications

Product Overview

Suitable Applications:	low voltage analog signals (4-20ma, 0-10v, ...); low voltage control (24v, ...); line level audio; panel wiring
------------------------	---

Product Life Cycle

Life Cycle:	Discontinued - the product is no longer manufactured
Discontinuation Announcement Date:	1999-02-19

Construction Details

Conductor

Size	Stranding	Material
16	19x29	TC - Tinned Copper

Insulation

Material	Nom. Insulation Diameter	Color Code
PVC - Polyvinyl Chloride	0.113 in (2.87 mm)	Orange, Black, Orange w/Black Stripe

Outer Shield

Material
No Shield

Outer Jacket

Nom. Diameter
0.243 in

Electrical Characteristics

Voltage

UL Voltage Rating
300 V RMS (UL AWM Style 1007)

Mechanical Characteristics

Temperature

UL Temperature	Operating
80°C (UL AWM Style 1007)	-40°C To +80°C

Max. Pull Tension:	97 lbs (44 kg)
Bulk Cable Weight:	38 lbs/1000ft (57 kg/km)

Standards and Compliance

Environmental Suitability:	Indoor (Not Riser or Plenum), Indoor
----------------------------	--------------------------------------

Flammability / Reaction to Fire:	VW-1
AWM Compliance:	AWM 1007 (300 V 80°C)
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:	Revision Number: 0.335 Revision Date: 07-30-2026
----------------------	--

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC
9498 0001000	None	Reel	1,000 ft	612825239970

© 2026 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.