

1100 GS6 PANEL KIT - 2U



OBSOLETE

Replaced By:

7602068471100-U-GS6-48

1100 GS6 PANEL - 48 PORT

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	SYSTIMAX®
Product Type	RJ45 patch panel
Product Series	NA

General Specifications

ANSI/TIA Category	NA
Cable Type	Unshielded
Color	Black
Intelligence Type	Passive
Panel Style	Flat
Rack Type	EIA 19 in
Rack Units	2
Total Ports, quantity	48

Dimensions

Height	88.1 mm 3.469 in
Width	482.6 mm 19 in
Depth	119.38 mm 4.7 in
Depth, with cable management	113.3 mm 4.461 in

Material Specifications

Material Type	Powder-coated steel
---------------	---------------------

Environmental Specifications

Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Relative Humidity	Up to 95%, non-condensing
Safety Standard	UL cUL

Packaging and Weights

Packaging Material	Eco-friendly, single-use plastics-free
Packaging quantity	1

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant/Exempted
UK-ROHS	Compliant/Exempted

