



SYSTIMAX 360™ Intelligent Shielded Angled Modular Panel,
Empty, 1U, 24 port, Silver

- Only to be used with InstaPATCH® Copper assemblies
- Does not fit MGS600S jacks

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	SYSTIMAX®
Product Type	Copper patch panel
Product Brand	imVision®

General Specifications

ANSI/TIA Category	NA
Cable Type	Shielded
Color	Cool gray Satin chrome
Conductor Type	Solid Stranded
Intelligence Type	iPatch® enabled
Panel Style	Angled
Rack Type	EIA 19 in
Rack Units	1
Total Ports, quantity	24
Wiring	T568A T568B

Dimensions

Height	44.45 mm 1.75 in
Width	482.6 mm 19 in
Depth, with cable management	266.7 mm 10.5 in

Compatible Conductor Gauge, solid	22 AWG 24 AWG
Compatible Conductor Gauge, stranded	22 AWG 24 AWG

Material Specifications

Material Type	High-impact, flame retardant, thermoplastic Powder-coated steel
---------------	---

Environmental Specifications

Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Relative Humidity	Up to 95%, non-condensing
Flammability Rating	UL 94 V-0
Safety Standard	UL cUL

Packaging and Weights

Packaging Material	Eco-friendly, single-use plastics-free
Packaging quantity	1