



SYSTIMAX 360™ GigaSPEED X10D® Shielded Angled Modular Panel, 1U, 24 port, Silver

This product will be discontinued on: July 31, 2026

Product Classification

|                       |                                                                     |
|-----------------------|---------------------------------------------------------------------|
| Regional Availability | Asia   Australia/New Zealand   EMEA   Latin America   North America |
| Portfolio             | SYSTIMAX®                                                           |
| Product Type          | RJ45 patch panel                                                    |
| Product Brand         | GigaSPEED X10D®   SYSTIMAX 360™                                     |
| Product Series        | NA                                                                  |

General Specifications

|                       |               |
|-----------------------|---------------|
| ANSI/TIA Category     | NA            |
| Cable Type            | Shielded      |
| Color                 | Silver        |
| Intelligence Type     | iPatch® ready |
| Panel Style           | Angled        |
| Rack Type             | EIA 19 in     |
| Rack Units            | 1             |
| Total Ports, quantity | 24            |
| Wiring                | T568A   T568B |

Dimensions

|        |                   |
|--------|-------------------|
| Height | 43.7 mm   1.72 in |
|--------|-------------------|

|                              |                    |
|------------------------------|--------------------|
| Width                        | 482.6 mm   19 in   |
| Depth, with cable management | 271 mm   10.669 in |

Material Specifications

|               |                                                                   |
|---------------|-------------------------------------------------------------------|
| Material Type | High-impact, flame retardant, thermoplastic   Powder-coated steel |
|---------------|-------------------------------------------------------------------|

Environmental Specifications

|                       |                                      |
|-----------------------|--------------------------------------|
| Operating Temperature | -10 °C to +60 °C (+14 °F to +140 °F) |
| Storage Temperature   | -40 °C to +70 °C (-40 °F to +158 °F) |
| Relative Humidity     | Up to 95%, non-condensing            |
| Flammability Rating   | UL 94 V-0                            |
| Safety Standard       | UL   cUL                             |

Packaging and Weights

|                    |                                        |
|--------------------|----------------------------------------|
| Packaging Material | Eco-friendly, single-use plastics-free |
| Packaging quantity | 1                                      |

Regulatory Compliance/Certifications

| Agency        | Classification                                                                                                                 |
|---------------|--------------------------------------------------------------------------------------------------------------------------------|
| CHINA-ROHS    | Below maximum concentration value                                                                                              |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system                                                 |
| REACH-SVHC    | Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a> |
| ROHS          | Compliant                                                                                                                      |
| UK-ROHS       | Compliant                                                                                                                      |

