



SYSTIMAX 360™ Shielded Modular Panel, Empty, 1U, 24 port,  
Silver

- Only to be used with InstaPATCH® Copper assemblies

Product Classification

|                       |                                                                     |
|-----------------------|---------------------------------------------------------------------|
| Regional Availability | Asia   Australia/New Zealand   EMEA   Latin America   North America |
| Portfolio             | SYSTIMAX®                                                           |
| Product Type          | Copper patch panel                                                  |
| Product Brand         | GigaSHIELD X10D®                                                    |

General Specifications

|                       |                          |
|-----------------------|--------------------------|
| ANSI/TIA Category     | NA                       |
| Cable Type            | Shielded                 |
| Color                 | Cool gray   Satin chrome |
| Conductor Type        | Solid   Stranded         |
| Panel Style           | Straight                 |
| Rack Type             | EIA 19 in                |
| Rack Units            | 1                        |
| Total Ports, quantity | 24                       |
| Wiring                | T568A   T568B            |

Dimensions

|                                   |                     |
|-----------------------------------|---------------------|
| Height                            | 44.8 mm   1.764 in  |
| Width                             | 482.6 mm   19 in    |
| Depth, with cable management      | 169.8 mm   6.685 in |
| Compatible Conductor Gauge, solid | 22 AWG   26 AWG     |

Compatible Conductor Gauge, stranded24 AWG | 26 AWG

Material Specifications

Material TypeHigh-impact, flame retardant, thermoplastic | PC+ABS | Powder-coated steel

Environmental Specifications

Operating Temperature-10 °C to +60 °C (+14 °F to +140 °F)

Storage Temperature-40 °C to +70 °C (-40 °F to +158 °F)

Relative HumidityUp to 95%, non-condensing

Flammability RatingUL 94 V-0

Packaging and Weights

Packaging MaterialEco-friendly, single-use plastics-free

Packaging quantity1

Regulatory Compliance/Certifications

| Agency     | Classification                                                                                                                 |
|------------|--------------------------------------------------------------------------------------------------------------------------------|
| CHINA-ROHS | Above maximum concentration value                                                                                              |
| CHINA-ROHS | Below maximum concentration value                                                                                              |
| REACH-SVHC | Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a> |
| ROHS       | Compliant/Exempted                                                                                                             |
| ROHS       | Compliant                                                                                                                      |
| UK-ROHS    | Compliant/Exempted                                                                                                             |
| UK-ROHS    | Compliant                                                                                                                      |

