



SYSTIMAX 360™ Shielded Modular Panel, Empty, 2U, 48 port,
Silver

- Only to be used with InstaPATCH® Copper assemblies

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	SYSTIMAX®
Product Type	Copper patch panel
Product Brand	GigaSHIELD X10D®

General Specifications

ANSI/TIA Category	NA
Cable Type	Shielded
Color	Cool gray Satin chrome
Conductor Type	Solid Stranded
Panel Style	Straight
Rack Type	EIA 19 in
Rack Units	2
Total Ports, quantity	48
Wiring	T568A T568B

Dimensions

Height	89.2 mm 3.512 in
Width	482.6 mm 19 in
Depth, with cable management	172.4 mm 6.787 in
Compatible Conductor Gauge, solid	22 AWG 26 AWG

Compatible Conductor Gauge, stranded

24 AWG | 26 AWG

Material Specifications

Material Type

High-impact, flame retardant, thermoplastic | PC+ABS | Powder-coated steel

Environmental Specifications

Operating Temperature

-10 °C to +60 °C (+14 °F to +140 °F)

Storage Temperature

-40 °C to +70 °C (-40 °F to +158 °F)

Relative Humidity

Up to 95%, non-condensing

Flammability Rating

UL 94 V-0

Packaging and Weights

Packaging Material

Eco-friendly, single-use plastics-free

Packaging quantity

1

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant/Exempted
UK-ROHS	Compliant/Exempted

