



SYSTIMAX 360™ Shielded Angled Modular Panel, Empty, 1U, 24 port, Silver

- Only to be used with InstaPATCH® Copper assemblies

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	SYSTIMAX®
Product Type	Copper patch panel
Product Brand	GigaSHIELD X10D®

General Specifications

ANSI/TIA Category	NA
Cable Type	Shielded
Color	Cool gray Satin chrome
Conductor Type	Solid Stranded
Panel Style	Angled
Rack Type	EIA 19 in
Rack Units	1
Total Ports, quantity	24
Wiring	T568A T568B

Dimensions

Height	44.7 mm 1.76 in
Width	482.6 mm 19 in
Depth, with cable management	274.7 mm 10.815 in
Compatible Conductor Gauge, solid	22 AWG 26 AWG

Compatible Conductor Gauge, stranded24 AWG | 26 AWG

Material Specifications

Material TypeHigh-impact, flame retardant, thermoplastic | PC+ABS | Powder-coated steel

Environmental Specifications

Operating Temperature-10 °C to +60 °C (+14 °F to +140 °F)

Storage Temperature-40 °C to +70 °C (-40 °F to +158 °F)

Relative HumidityUp to 95%, non-condensing

Flammability RatingUL 94 V-0

Packaging and Weights

Packaging MaterialEco-friendly, single-use plastics-free

Packaging quantity1

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant/Exempted
ROHS	Compliant
UK-ROHS	Compliant/Exempted
UK-ROHS	Compliant

