

SYSTIMAX 360™ PATCHMAX® Panel Kit, 2U, 48 port



OBSOLETE

Replaced By:

760117366 360-PM- GS3-2U-48	SYSTIMAX 360™ GigaSPEED XL® PATCHMAX® GS3 Category 6 U/UTP Patch Panel, 2U, 48 port, silver
760128207 360-PM- GS6-2U-48	SYSTIMAX 360™ GigaSPEED X10D® PATCHMAX® GS6 Unshielded Patch Panel, Cat6A, 48 port, Silver

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	SYSTIMAX®
Product Type	RJ45 patch panel
Product Brand	GigaSPEED X10D®
Product Series	NA

General Specifications

ANSI/TIA Category	NA
Cable Type	Unshielded
Color	Silver
Intelligence Type	iPatch® ready
Panel Style	Flat

Rack Type	EIA 19 in
Rack Units	2
Total Ports, quantity	48

Dimensions

Height	88.1 mm 3.469 in
Width	482.6 mm 19 in
Depth, with cable management	264.7 mm 10.421 in

Material Specifications

Material Type	High-impact, flame retardant, thermoplastic Powder-coated steel
---------------	---

Environmental Specifications

Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Relative Humidity	Up to 95%, non-condensing
Flammability Rating	UL 94 V-0

Packaging and Weights

Packaging Material	Eco-friendly, single-use plastics-free
Packaging quantity	1

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant

UK-ROHS

Compliant

