

Copper Cable, category 5e, 4 pair, U/UTP, CM rated, 24 AWG, 1000 ft, blue

This product will be discontinued on: November 30, 2026

Product Classification

Regional Availability	Asia
Portfolio	NETCONNECT®
Product Type	Twisted pair cable
Product Series	510 Series

General Specifications


Product Number	510M
ANSI/TIA Category	5e
Cable Component Type	Horizontal
Cable Type	U/UTP (unshielded)
Conductor Type, singles	Solid
Conductors, quantity	8
Jacket Color	Blue
Pairs, quantity	4
Transmission Standards	ANSI/TIA-568.2-D CENELEC EN 50288-6-1 ISO/IEC 11801 Class D

Dimensions

Cable Length	304.8 m 1000 ft
Diameter Over Jacket, nominal	4.902 mm 0.193 in

Conductor Gauge, singles24 AWG

Cross Section Drawing



Electrical Specifications

Operating Voltage, maximum	80 V
Remote Powering	Fully complies with the recommendations set forth by IEEE 802.3bt (Type 4) for the safe delivery of power over LAN cable when installed according to ISO/IEC 14763-2, CENELEC EN 50174-1, CENELEC EN 50174-2 or TIA TSB-184-A

Electrical Performance

CS CommScope value	IL Insertion Loss (dB/100m)	ACR Attenuation to Crosstalk Ratio (dB/100m)
Std Standard value (listed under the Transmission Standards in the Electrical Specifications above)	RL Return Loss (dB)	ACRF Attenuation to Crosstalk Ratio - Far End (dB/100m)
Typ Typical value	NEXT Near End Crosstalk (dB/100m)	PSACR Power Sum Attenuation to Crosstalk Ratio (dB/100m)
	PSNEXT Power Sum Near End Crosstalk (dB/100m)	PSACRF Insertion Loss (dB/100m)

FREQUENCY	IL TYP	IL CS	IL STD	NEXT TYP	NEXT CS	NEXT STD	ACR TYP	ACR CS	ACR STD	PSNEXT TYP	PSNEXT CS	PSNEXT STD	PSACR TYP	PSACR CS	PSACR STD	ACRF TYP	ACRF CS	ACRF STD	PSACRF TYP	PSACRF CS	PSACRF STD	RL TYP	RL CS	RL STD
1.00 MHz			2			74.3			72.3			72.3			70.3			67.8			64.8			20
4.00 MHz			3.8			65.3			61.5			63.3			59.5			55.8			52.8			23
8.00 MHz			5.3			60.8			55.5			58.8			53.5			49.7			46.7			24.5
10.00 MHz			6			59.3			53.3			57.3			51.3			47.8			44.8			25
16.00 MHz			7.6			56.2			48.6			54.2			46.6			43.7			40.7			25
20.00 MHz			8.5			54.8			46.3			52.8			44.3			41.8			38.8			25
25.00 MHz			9.5			53.3			43.8			51.3			41.8			39.8			36.8			24.3
31.25 MHz			10.7			51.9			41.2			49.9			39.2			37.9			34.9			23.6
62.50 MHz			15.4			47.4			32			45.4			30			31.9			28.9			21.5
100.00 MHz			19.8			44.3			24.5			42.3			22.5			27.8			24.8			20.1
200.00 MHz			29			39.8			10.8			37.8			8.8			21.8			18.8			18
250.00 MHz			32.8			38.3			5.5			36.3			3.5			19.8			16.8			17.3

Material Specifications

Conductor Material	Bare copper
Insulation Material	Polyolefin
Jacket Material	PVC

Environmental Specifications

Operating Temperature	-20 °C to +60 °C (-4 °F to +140 °F)
-----------------------	-------------------------------------

Packaging and Weights

Packaging TypeReelex

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

