



Copper Cable, category 5e, 4 pair, UTP, 350 MHz, CMR rated, 1000 ft pull-box, blue

This product will be discontinued on: November 30, 2026

Product Classification

Regional Availability	Asia
Portfolio	NETCONNECT®
Product Type	Twisted pair cable
Product Series	520 Series

General Specifications

Product Number	520R
ANSI/TIA Category	5e
Cable Component Type	Horizontal
Cable Type	U/UTP (unshielded)
Conductor Type, singles	Solid
Conductors, quantity	8
Jacket Color	Blue
Pairs, quantity	4
Transmission Standards	ANSI/TIA-568.2-D CENELEC EN 50288-6-1 ISO/IEC 11801 Class D

Dimensions

Cable Length	304.8 m 1000 ft
Diameter Over Jacket, nominal	4.699 mm 0.185 in

Conductor Gauge, singles24 AWG

Electrical Specifications

Operating Voltage, maximum80 V

Remote PoweringFully complies with the recommendations set forth by IEEE 802.3bt (Type 4) for the safe delivery of power over LAN cable when installed according to ISO/IEC 14763-2, CENELEC EN 50174-1, CENELEC EN 50174-2 or TIA TSB-184-A

Safety Voltage Rating300 V

Electrical Performance

CS CommScope value	IL Insertion Loss (dB/100m)	ACR Attenuation to Crosstalk Ratio (dB/100m)
Std Standard value	RL Return Loss (dB)	ACRF Attenuation to Crosstalk Ratio - Far End (dB/100m)
(listed under the Transmission Standards in the Electrical Specifications above)	NEXT Near End Crosstalk (dB/100m)	PSACR Power Sum Attenuation to Crosstalk Ratio (dB/100m)
Typ Typical value	PSNEXT Power Sum Near End Crosstalk (dB/100m)	PSACRF Insertion Loss (dB/100m)

FREQUENCY	IL TYP	IL CS	IL STD	NEXT TYP	NEXT CS	NEXT STD	ACR TYP	ACR CS	ACR STD	PSNEXT TYP	PSNEXT CS	PSNEXT STD	PSACR TYP	PSACR CS	PSACR STD	ACRF TYP	ACRF CS	ACRF STD	PSACRF TYP	PSACRF CS	PSACRF STD	RL TYP	RL CS	RL STD
1.00 MHz			2			74.3			72.3			72.3			70.3			67.8			64.8			20
4.00 MHz			3.8			65.3			61.5			63.3			59.5			55.8			52.8			23
8.00 MHz			5.3			60.8			55.5			58.8			53.5			49.7			46.7			24.5
10.00 MHz			6			59.3			53.3			57.3			51.3			47.8			44.8			25
16.00 MHz			7.6			56.2			48.6			54.2			46.6			43.7			40.7			25
20.00 MHz			8.5			54.8			46.3			52.8			44.3			41.8			38.8			25
25.00 MHz			9.5			53.3			43.8			51.3			41.8			39.8			36.8			24.3
31.25 MHz			10.7			51.9			41.2			49.9			39.2			37.9			34.9			23.6
62.50 MHz			15.4			47.4			32			45.4			30			31.9			28.9			21.5
100.00 MHz			19.8			44.3			24.5			42.3			22.5			27.8			24.8			20.1
200.00 MHz			29			39.8			10.8			37.8			8.8			21.8			18.8			18
250.00 MHz			32.8			38.3			5.5			36.3			3.5			19.8			16.8			17.3

Material Specifications

Conductor Material	Bare copper
Insulation Material	Polyolefin
Jacket Material	PVC

Environmental Specifications

Operating Temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Environmental Space	Non-plenum

Packaging and Weights

Cable weight	32.74 kg/km 22 lb/kft
Packaging Type	Pull box