


DS-2DE3C204MWG1H-E**2 MP 4X Smart Hybrid Light AI-ISP Mini PTZ Network Camera**

Powered by

DarkFighter

Hikvision DS-2DE3C204MWG1-E 2MP 4 × IR Network Speed Dome adopts 1/2.8" progressive scan CMOS chip. With the 4 × optical zoom lens, the camera offers more details over expansive areas.

This series of cameras can be widely used for wide ranges of high-definition, such as rivers, roads, railways, airports, squares, parks, scenic spots, and venues, etc.

Hikvision has been dedicated to develop products with security since established.

Hikvision always follows security by design principle and has adopted many methods of security technologies into our product development lifecycle, including terminal security, data security, application security, network security, and privacy protection. In the meantime, the security technologies used by Hikvision are all in compliance with local applicable laws and safety regulations. These security measures could enhance product's cyber security protection capability and protect your devices as well as your data from malicious cyber attacks.

- High quality imaging with 2 MP resolution
- Excellent low-light performance with powered-by-DarkFighter technology
- Secures an expansive area with 4× optical zoom and 16× digital zoom
- Supports WDR, HLC, BLC, 3D DNR, defog, regional exposure, regional focus
- Supports 12V DC & PoE+
- Support Human and Vehicle Detection

▪ Specification

Camera	
Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	Color: 0.01 Lux @ (F1.5, AGC ON), B/W: 0.005 Lux @ (F1.5, AGC ON), 0 Lux with IR
Shutter Speed	1 s to 1/30,000 s
Slow Shutter	Yes
Zoom	4 × optical, 16 × digital
Day & Night	ICR
Max. Resolution	1920 × 1080
Lens	
Focus	auto, manual, semi-auto
Focal Length	2.8 to 12 mm
Zoom Speed	Approx. 3.3 s
FOV	Horizontal field of view: 93.5° to 29.1°, vertical field of view: 49.2° to 16.4°, diagonal field of view: 111.9° to 33.4°
Aperture	Max. F1.5
Illuminator	
Supplement Light Type	IR, White Light
Smart Supplement Light	Yes
Supplement Light Range	White light distance: up to 30 m, IR distance: up to 40 m
PTZ	
Movement Range (Pan)	0° to 350°
Movement Range (Tilt)	0° to 90°
Pan Speed	Pan speed: configurable from 1° to 35°/s, preset speed: 35°/s
Tilt Speed	Tilt speed: configurable from 1° to 30°/s, preset speed 30°/s
Proportional Pan	Yes
Presets	300
Patrol Scan	8 patrols, up to 32 presets for each patrol
Power-off Memory	Yes
Park Action	Preset, pattern scan, patrol scan, auto scan, tilt scan, random scan, frame scan, panorama scan
3D Positioning	Yes
PTZ Status Display	Yes
Scheduled Task	Preset, pattern scan, patrol scan, auto scan, tilt scan, random scan, frame scan, panorama scan, dome reboot, dome adjust
Video	
Third Stream	50 Hz: 25 fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 576, 640 × 480, 352 × 288) 60 Hz: 10 fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 480, 640 × 480, 352 × 240)
Region of Interest (ROI)	1 fixed regions for each stream
Main Stream	50 Hz: 25 fps (1920 × 1080, 1280 × 960, 1280 × 720) 60 Hz: 30 fps (1920 × 1080, 1280 × 960, 1280 × 720)
Sub-Stream	50 Hz: 25 fps (704 × 576, 640 × 480, 352 × 288) 60 Hz: 30 fps (704 × 480, 640 × 480, 352 × 240)
Video Compression	H.265, H.264, MJPEG
Video Bit Rate	32 kbps to 16384 kbps
H.264 Type	main profile, baseline profile, high profile

H.265 Type	main profile
Scalable Video Coding (SVC)	Yes
Audio	
Audio Compression	G.711,G.722.1,G.726,MP2L2,PCM,AAC,MP3
Audio Bit Rate	64 Kbps (G.711ulaw/G.711law),8 to 160 Kbps (MP3),32 to 160 Kbps (MP2L2),16 to 64Kbps (AAC-LC),16 Kbps (G.722.1),16 Kbps (G.726)
Audio Sampling Rate	8 kHz,16 kHz
Environment Noise Filtering	Yes
Network	
API	ONVIF (ProfileS, ProfileG, ProfileT),ISAPI,SDK,ISUP
Network Storage	NAS (NFS, SMB/ CIFS), ANR
Protocols	TCP/IP,ICMP,HTTP,FTP,DDNS,RTP,RTSP,RTCP,PPPoE,NTP,UPnP,SMTP,SNMP,IGMP,QoS, IPv6,WebSockets,SSL/TLS,WebSocket,UDP
Simultaneous Live View	Up to 6 channels
User/Host	32
Security	complicated password>Password protection,HTTPS encryption,802.1X authentication (EAP-TLS, EAP-LEAP, EAP-MD5),watermark,IP address filter,WSSE and digest authentication for Open Network Video Interface, RTP/RTSP over HTTPS,basic and digest authentication for HTTP/HTTPS,control timeout settings,security audit log
Client	iVMS-4200,Hik-Connect
Web Browser	Chrome80+ , Firefox80+ , Safari13+ , Edge89
Image	
Image Settings	contrast,gain,saturation,sharpness,brightness,white balance,adjustable by client software or web browser
SNR	≥ 52 dB
Defog	Digital defog
Day/Night Switch	day, night, auto, scheduled-switch
Image Enhancement	BLC,HLC,3D DNR
Privacy Mask	24 programmable polygon privacy masks
Regional Focus	Yes
Regional Exposure	Yes
Image Parameters Switch	Yes
Interface	
Built-in Microphone	1 built-in microphone
Built-in Speaker	1 built-in speaker
Ethernet Interface	RJ45, self-adaptive 10M/100M Ethernet port
On-board Storage	Built-in memory card slot,support Micro SD/SDHC/SDXC, up to 512 GB
Reset	Yes
Event	
Basic Event	exception (network disconnected,IP address conflict,illegal login,HDD full,HDD error),Motion detection,video tampering alarm,audio exception detection
Smart Event	Line crossing detection,intrusion detection,region entrance detection,region exiting detection,loitering detection,people gathering detection,fast moving detection,parking detection,unattended baggage detection,object removal detection
Linkage	Upload to FTP/NAS/memory card,notify surveillance center,send email,trigger recording,trigger capture,white light flashing,audible warning,smart tracking

Deep Learning Function	
Face Capture	Detects up to 5 faces simultaneously, Uploads face with background and closed-up face pictures
Linkage and Tracking	
Smart Tracking	Yes
General	
General Function	mirror,password protection,watermark,IP address filter
Power	12 VDC, max.14W, PoE+
Operating Condition	-30 °C to 50 °C (-22 °F to 122 °F). Humidity 95% or less (non-condensing)
Material	PC+10%GF,ADC12
Dimension	227.8 mm × 218.4 mm × 154.9 mm (8.97" × 8.60" × 6.10")
Weight	Approx. 1.37 kg (3.02 lb.)
Approval	
Protection	IP66 (IEC 60529-2013)

▪ DORI

DORI	Detect	Observe	Recognize	Identify
Distance (Tele)	128.6 m (421.9 ft)	51.0m (167.3 ft)	25.7 m (84.3 ft)	12.9 m (42.3 ft)

The DORI (detect, observe, recognize, identify) distance gives the general idea of the camera ability to distinguish persons or objects within its field of view. It is calculated based on the camera sensor specification and the criteria given by EN 62676-4: 2015.





▪ Typical Application

Hikvision products are classified into three levels according to their anti-corrosion performance. Refer to the following description to choose for your using environment.

This model has NO SPECIFIC PROTECTION.

Level	Description
Top-level protection	Hikvision products at this level are equipped for use in areas where professional anti-corrosion protection is a must. Typical application scenarios include coastlines, docks, chemical plants, and more.
Moderate protection	Hikvision products at this level are equipped for use in areas with moderate anti-corrosion demands. Typical application scenarios include coastal areas about 2 kilometers (1.24 miles) away from coastlines, as well as areas affected by acid rain.
No specific protection	Hikvision products at this level are equipped for use in areas where no specific anti-corrosion protection is needed.

▪ Dimension



Camera Mounting Hole

Installation interface

See Far, Go Further



www.hikvision.com
support@hikvision.com

